



FALCON RIDGE

2515 Bypass Rd. Flemingsburg, KY 41041
606-845-7439

Instructions for Installation and Care of
Mahindra Roxor
Soft Rear Cargo Cover
MAH-ROXOR-RCC01

Notice: Do not smoke inside the cab or expose the enclosure to direct flames. Cab is Flammable.

1. Be sure to read these instructions thoroughly before opening and installing the enclosure. The installation is best done when the temperature is 70 degrees F. or warmer. The temperature affects the adhesive Velcro, if conditions prevent installing in warmer weather it helps to store the adhesive Velcro at room temperature prior to installation.
2. Carefully open the carton and remove the enclosure on a large flat surface that is clean and free of dirt.
3. Check over the parts included in the carton with the parts list shown below:

Adhesive Velcro Hook Strips:

					<u>Rear Cargo Cover</u>
“	“	“	“	2 each-----	52”
“	“	“	“	1 each-----	45”
“	“	“	“	2 each-----	32”
Cab Enclosure				3 panels	

The cab will be put together using the following parts and in this order.

- 1) Rear Side Panels
- 2) Rear Cargo Cover

REAR SIDE PANELS

1. The Rear Side Panels are very simple to install. Take the 52" adhesive strips and install them on the top of the rear downbars as shown in the photo below



2. Now just line up the top corner so it overlaps the Velcro sewn to the outside of the door and attach it to the door and the roll cage. Pull it down so the magnets are on the sides of the bed and that it. See photos below.



REAR CARGO COVER

3. Begin by placing the 45" Velcro strip across the top rear bar. Place it so the Velcro is facing upward. See photo below.



4. Simply attach it to all the Velcro starting with the top of the Rear Window. Make sure it is centered correctly and at the right height. Then attach the sides to the double-sided tab of the rear side covers and the bottom will hold to the bed using magnets. See photo below.



Cleaning and Storage Recommendations:

1. Before removing the Falcon Ridge Cab for storage, make sure it is very clean in order to prevent scratching of the window panels. Clean with a soft rag or sponge using a mild liquid detergent soap and warm water solution. Never rub the windows with a dry cloth or rag! Let the Cab dry thoroughly before attempting to roll for storage.
2. It is important that the Cab be rolled up for storage rather than folding. Folding will cause damage to the windows!!! Carefully roll up the Cab similar to the way it was when it was packed at the factory.

On a large, clean and flat surface, fold the doors over the rear panel first, then, interleave the top and windshield on top of the doors. Begin rolling the Cab into a roll approximately 8 inches in diameter. Put the rolled Cab back into the carton for storage at a normal room temperature. It is best not to expose the Cab to either extreme hot or cold temperatures when storing.

3. A special cleaner conditioner is available from Falcon Ridge that will greatly increase the service life of the Cab Enclosure. In addition, if additional hook and loop sets are needed, they can also be ordered.